

POLISPEC VIS PORTABLE

Portable visible-range spectrophotometer covering 400–700 nm for colour measurement in laboratory and at-line applications. Features diffuse/0° measurement geometry, automatic internal references and Polidata software.



Dim. 22.8 x 21.4 x 8.8 cm (l x h x w)

Weight 2.5 kg

Material Anodised Aluminium
(standard)

IP protection IP68 / IP9K



Sensor CMOS, 256 pixels

Spectral range 400-700 nm

Average numerical resolution 1.6 nm

Average Optical Resolution HWHM < 7 nm

Optical signal collection Direct optical coupling

Power supply 12 Vdc ± 20%; Battery 3.35Ah

Power consumption <30W

Operating temperature From -15°C to +46°C



Type of measurement Reflectance; Transmittance*
*may require external accessories

Measurement geometry Diffuse/0°

Measurement references Internal and automatic

Communication channels WiFi + RS422 (standard)

Source type Replaceable halogen lamp



Options

At-line accessories



Command and signals

Hardware buttons dedicated to the measurement and to the references acquisition; Light and acoustic signalling of the acquisition status



Software

poliDATA Data acquisition and chemometric prediction software compatible with the SensoLogic and UCal Chemometric suites.



polispec.com // itphotonics.com

ITPhotonics S.r.l.: via Astico 39, 36030 Fara Vicentino (VI) - Italia
T. (+39) 0445-1925221 || M. info@itphotonics.com